



| | | |
|------|-------|---|
| | | 2 |
| | | 2 |
| | | 3 |
| | | 4 |
| | | 5 |
| DTRO | | 6 |
| | | 7 |

DTRO

V101 P101 P102 M101

1

V101 G101 G103 ZX101 G102

G111 G112 P101 P102

2

V101 G101 G103 ZX101 G102

G111 G112 P101 P102

ZX101

V101

3

- 1.
2. <15L
3. CAT
75Bar
- 4.
5. SDI 20
6. DTRO 210 209 9.4
100 200L/H, 50 200L
7. 316L
- 8.

DTRO

| | | | | | | |
|----|--|-----------------|--------|---|-----|---------|
| 1 | | 100L | SS316 | | 1 | |
| 2 | | Q=1m /H, H=32m | SS316 | | 1 | |
| 3 | | 6 5 m PP | | | 1 | |
| 4 | | Q=1m /H, H=700m | SS316 | | 1 | wanner |
| 5 | | B35 5.5KW | | | 1 | ABB |
| 6 | | 75Bar RO | | | 209 | DOW |
| 7 | | | | | 1 | |
| 8 | | Y60 0-10MPa | SS316 | | 2 | |
| 9 | | 0-10MPa | SS316 | | 1 | DANFOSS |
| 10 | | 0-7L/M | | | 1 | |
| 11 | | 0-30L/M | | | 1 | |
| 12 | | 5.5KW | | | 1 | |
| 13 | | 1/4" | SS316 | | 1 | |
| 14 | | 0.2L | SS316 | | 1 | |
| 15 | | 1/4" | SS316 | | 1 | |
| 16 | | | SS304 | | 1 | |
| 17 | | | SS316L | | 1 | |
| 18 | | | | | 1 | |
| 19 | | | | | 1 | |
| | | | 1 | 1 | | |

: 0000 .00 ()

1

2

3

17%

DTRO

| | | |
|------|----|------------|
| DTRO | | |
| | | WTM-DT210D |
| | | |
| | | |
| | | 209 9.4 |
| | | 3.0-7.5Mpa |
| | | 7.5MPa |
| | * | 99.5% |
| | | 5 40 |
| | | 45 |
| | PH | 2 11 |
| | pH | 1 12 |
| | | <15L |
| | | 50-200L |
| | | 20-25% |
| | | 120-200L/H |
| | | Q=1m /H |
| | DT | |
| | | |

*

15%

NaCl 32,000mg/L @800 psi (5.5MPa)

